



# RP *Strike-X*™

variant **Can-Am Maverick X3 Turbo R**



[www.RPAMS.com](http://www.RPAMS.com)  
Bringing more **ASSETS** to the fight!



# RP Strike-X™

variant Can-Am Maverick X3 Turbo R

## Standard Configuration

### RP Strike-X™

- RP Super Grit Texture Coating, tan, black, camo
- High-Capacity, multi-modal tactical payload flatbed
- Multi-Modal tailgate system for multiple tactical payload track configurations with optional MEDEVAC integration
- Tactical assault push bumper with strut integrated payload track system and aerial transport tie-downs
- Forward/rear 2-inch receiver
- RP SOF Series IV Magnum, 8-PLY tires, 30x10x14
- Raceline Black Mambo beadlock wheels, and extended lug nuts
- MOLLE Soft Roof, 1000D Cordura
- MOLLE Soft Door Panels, 1000D Cordura

### RECOMMENDED OPTIONS:

- High-Load tactical team standoff nerf bar assembly/rock slider with stow and lock mode for air transport
- RP modular ammo/fuel can/payload assembly
- Additional 12VDC & 24VDC outlets
- Elka Suspension model specific Stage 5 race-level high-performance shocks
- Baja Designs blackout/IR lights & light bars

### OPTIONAL EQUIPMENT:

- RP Powdercoating, custom colors available
- Hydrographic finishes, custom colors and patterns available
- RP modular front cargo rack
- RP SOF Spartan Series 12-PLY tires, 29x9x14 Front/29x11x14 Rear
- HID/LED light illumination
- RP Fatigue Mitigation Tactical Seat System
- Integrated seat hydration packs
- RP 4-point static retractable quick release harness kit
- SatFi communication system/bundle package
- Half windshield
- MEDEVAC integration
- RP litter restraint, multi-modal with configurable rail system
- PowerAll® jump start system
- Initial spare parts kit



## VEHICLE SPECIFICATIONS

- 900 cc, 154 Hp, Rotax® ACE (Advanced Combustion Efficiency) turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
- Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P. Tri-Mode Dynamic Power Steering (DPS)
- Double A-arm front suspension with sway bar and 4-link torsional trailing A-arm X (TTX) with sway bar
- Selectable 2WD / 4WD shaft driven with Visco-Lok X auto-locking front differential
- Dual-phase 980 steel cage, fully welded
- Anti-Theft: Digitally Encoded Security System (D.E.S.S.™)

DRY WEIGHT	1,790-1,990 lb (depending on options)
DIMENSIONS	
X3 & X3ds	131 (L) x 64 (W) x 66 in (H) 332.7 (L) x 162.5 (W) x 167.6 cm (H)
X3rs	132 (L) x 72 (W) x 67 in (H) 335.3 (L) x 182.9 (W) x 170.2 cm (H)
WHEELBASE	102 in (259.1 cm)
GROUND CLEARANCE	
X3 & X3ds	14 in (35.6 cm)
X3rs	15 in (38.1 cm)
FUEL CAPACITY	10.5 gal (40 L)
PAYLOAD CAPACITY	1,500 lb
REAR BED CAPACITY	600 lb
OPTIONAL FRONT RACK CAPACITY	200 lb
TOWING CAPACITY	1,500 lb



### INFORMATION & DEALER INQUIRIES

Terry Wilmeth 971-237-3217, Nick Mooers 541-914-7543 or [CustomerService@RPAMS.com](mailto:CustomerService@RPAMS.com)



**RP Advanced Mobile Systems**

Veteran and Minority Owned Business

11160 SW Durham Lane, Suite 3 | McMinnville, Oregon 97128 | phone: 503-434-9446 | fax: 503-217-6080

[www.RPAMS.com](http://www.RPAMS.com)

All pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication and are subject to change without notice. RP Advanced Mobile Systems, LLC assumes no responsibility for any inaccuracies, opinion, errors or omissions in those publications, nor fitness of purpose and non-infringement of intellectual property.

REV-02272017